

Intergrain UltraPrep Timber Cleaner

AU_DW02614

Part A	55294814
--------	----------

Description

Intergrain UltraPrep™ Timber Cleaner is a high strength timber treatment that contains oxalic acid and citric acid, both naturally occurring, bio-degradable acids. Use Intergrain UltraPrep Timber Cleaner to remove surface contaminants prior to coating, the cleaner will help to restore and prepare weathered, grey, rust or tannin stained, mould or mildew affected timber to a clean appearance ready for coating.

Features

- High strength concentrate
- Contains natural bio-degradable acids


Uses

Prior to coating all exterior timber including decking, outdoor furniture, cladding, screening and fences.
Not suitable for interior applications.

Precautions And Limitations

Exterior use only. Not suitable for interior use.
Wear waterproof gloves and safety glasses.
Avoid contact with painted, glass, concrete or metal surfaces and vegetation. Protect areas not to be cleaned.
May be corrosive to metals. Rinse off thoroughly if contact occurs.

Typical Properties

V.O.C. Level	<10g/L	Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.
Clean Up	 Water		
Application Method	Other: Stiff bristle brush.		
Application Conditions	Min	Max	Recommended
	Wet Film Per Coat (microns)		
	Dry Film Per Coat (microns)		
	Recoat Time (min)		
	Theoretical Spread Rate (m ² /L)	10	
Typical Properties Notes	<p>MIX RATIO 1 part UltraPrep Timber Cleaner to 4 parts water</p> <p>COVERAGE Up to 10m²/L of concentrate.</p>		

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Remove surface dirt by sweeping or washing down with water.
Application Procedure And Equipment	<ul style="list-style-type: none"> Shake Intergrain UltraPrep Timber Cleaner thoroughly. Mix ONE part Intergrain UltraPrep Timber Cleaner to FOUR parts water in a plastic container. For severely stained surfaces a stronger solution or repeat applications may be necessary. Tannin rich timbers may also require repeat applications; wash until the water used to rinse off is clear. Wet the timber surfaces to be cleaned with water. Apply Intergrain UltraPrep Timber Cleaner mixture generously to the timber with a stiff bristle brush. Scrub the timber vigorously. Spot cleaning should be avoided to prevent patchy results. Leave mixture on the timber for 10-15 minutes. If necessary, apply more mixture to keep timber damp throughout this period, do not allow mixture to dry. Rinse off surface thoroughly using maximum pressure from a garden hose or using a high pressure water cleaner (recommended for large areas or badly discoloured timber). Failure to thoroughly rinse off the mixture may result in timber discolouration under clear finishes. <p>Note: After cleaning, some timber species will appear lighter due to loss of water soluble extractives. Richer colour is generally restored on application of the finish.</p> <p>HELP & ADVICE Australia – 1800 630 285 www.intergrain.com.au</p> <p>NZ – 0800 222 687 www.intergrain.co.nz</p> <p>For detailed project specifications or a Safety Data Sheet, contact Intergrain Help & Advice or visit our website.</p>

Health And Safety			
Using Safety Precautions	<p>HARMFUL IF SWALLOWED AND IN CONTACT WITH SKIN. CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE DAMAGE.</p> <p>Keep out of reach of children. Read the label before opening or using.</p> <p>Slippery when spilt. Avoid breathing mist, vapours or spray. Wear protective clothing, gloves and eye/face protection and suitable respiratory as required.</p> <p>Contaminated work clothing should not be allowed out of the workplace. Wash hands, face and all exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Store in a closed container. Store away from oxidising agents and foodstuffs. Avoid release to the environment.</p>	Health Effects	<p>SEE THE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.</p> <p>EMERGENCY INFORMATION (ALL HOURS): AUST – 1800 033 111; NZ – 0800 734 607.</p> <p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p>SWALLOWED: If swallowed, rinse mouth. Do NOT induce vomiting. Give a glass of water. Immediately call a POISON CENTRE or doctor/physician.</p> <p>EYE: If in eyes, hold eyes open, flush with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.</p> <p>INHALED: Remove from contaminated area – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered.</p>
Flammability	Non-flammable.	Fire Suppression	Non-combustible, however, if involved in a fire use water fog, foam or dry agents. Avoid breathing products of combustion.
Protective Equipment	Wear protective clothing, gloves and eye/face protection and suitable respiratory as required.	Storage	Keep out of reach of children. Store in a closed container. Store away from oxidising agents and foodstuffs.
Disposal	Dispose of contents/container in accordance with local, regional, national and international regulations.	Other	CONTAINS: 1-10% Oxalic Acid 1-10% Quaternary Ammonium Compound <1% d-Limonene
In the case of emergency, please call 1800 033 111			

Transport And Storage

Pack A	55294814
Size	Weight
1L	1.15Kg
4L	4.39Kg
10L	11.23Kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427